



# DALJIT ENGINEERING WORKS

## AUTOMATIC DOUBLE SPINDLE NUT TAPPING MACHINE



- SPECIFICATIONS**

CAPACITY	STROKE PER MINUTE	HP/R.P.M	WEIGHT APPROX.
1/8" (3mm)	250	1 H.P 1440 R.P.M	3.90 QTL
3/16"(5mm)	180	1 H.P.1440 R.P.M	3.90 QTL
1/4"(6mm)	140	1 H.P.1440 R.P.M	3.90 QTL
5/16"(8mm)	100	1.5 H.P.1440 R.P.M	4.50 QTL
3/8"(10mm)	80	1.5 H.P.1440 R.P.M	4.50 QTL
1/2"(12mm)	50	3 H.P.960 R.P.M	5.50 QTL
5/8"(16mm)	35	3 H.P.960 R.P.M	5.50 QTL
3/4"(20mm)	18	5 H.P.960 R.P.M	6 QTL
1"(24mm)	13	5 H.P.960 R.P.M	7 QTL
1 1/2" (38 mm)	2	7.50 H. P. 60 R.P.M. GEAR MOTOR	8.50 QTL

No Responsibility Is Taken For This Data, Which May Be Altered As Improvement In Manufacture Dictate.