



## HeBei Delong Fastener Manufacturing Co.,Ltd



### Company Introduction

Hebei Delong Fastener Manufacturing Co., Ltd. is located in Yongnian District, Handan City, Hebei Province, the distribution center of fasteners. It is close to Beijing Zhuhai Expressway, Beijing Guangzhou railway and national highway 107. It has convenient transportation and superior geographical location.

The company was founded in 2006. The company focuses on the R & D of high-end fasteners, with an annual production capacity of more than 8000 tons. It has first-class production equipment, technology and heat treatment equipment in Taiwan

Main Products: DR national standard Self Drilling Screw, DL Self Drilling Screw, Countersunk Self Drilling Screw, Walfer Self Drilling Screw, Nylon Self Drilling Screw; GB 93-76 (70#), new GB93-87 (65Mn), heavy GB7244-87 (65Mn), DIN127 (German standard), JIS b1251 (Japanese) spring washer; Large hole GB95, large washer GB96, national standard GB97, German standard DIN125, F436 high-strength washer (material 45#), GBT / 1230 steel structure washer. Various special non-standard fasteners can also be customized according to user needs. The products are widely used in construction, installation, steel structure engineering, automobile, machinery, electronics, agricultural machinery, etc. the products are sold to more than 20 provinces and cities in China and exported to Southeast Asia, Europe and America and other countries.

We adhere to the enterprise concept of "integrity-based, quality survival", provide best products and perfect after-sales service for our customers, and warmly hope to establish long-term and close cooperation with colleagues and customers all over the world.



# HeBei Delong Fastener Manufacturing Co.,Ltd

## Hex Head Self Drilling Screw

Compared with ordinary Screws, the self drilling screws have higher tenacity and maintenance force, and will not loosen for a long time after combination. The use, safe drilling and tapping are completed at one time, and the operation is simple. Thus, whereas a regular machine screw cannot tap its own hole in a metal substrate, Self Drilling Roofing Screw one can (within reasonable limits of substrate hardness and depth).Hex Washer Head Self Drilling Screw, Hex Roofing Screw, Self Drilling Screw

The self-drilling hex washer head screws available at DL Fasteners are suitable for any type of building or construction job. Hex Washer Head Self-drilling screws are best used for securing pieces of metal or attaching thin sheet metals to wood surfaces. All our hex flange head self-drilling screws are fully threaded for better security and weight distribution for lasting sturdiness and heavy-duty use.



Dia Size	#10(M4.8)	#12(M5.5)	#14(M6.3)
A/F	8MM	8MM	10MM
Flange Dia	10.5mm	11.0mm	13.5mm
Head Height	4.45mm	5.45mm	6.45mm
		3/4"	
		1"	
Length	1/2"	1-1/4"	
	5/8"	1-1/2"	3/4"
	3/4"	1-3/4"	1"
	1"	2"	1-1/4"
	1-1/4"	2-1/4"	1-1/2"
	1-1/2"	2-1/2"	2"
	1-3/4"	3"	
	2"	3-1/2"	

### Features

- 1.Precise cutting edges to improve drill performance with less effort
- 2.Point to thread design maximize pullout performance and minimizes backout

### Surface Treatment

- 1.White zinc plated
- 2.Blue-white zinc plated
- 3.Yellow zinc plated





# HeBei DeLong Fastener Manufacturing Co.,Ltd

## Truss Head Self Drilling Screw

Truss Head Self Drilling Screw are commonly used to attach cabinets to steel studs. They are also used in applications requiring low clearance above the head. Finally, Truss Head Tek Screw are used to assemble metal parts that will be used in humid environments.

In addition to securely holding thin materials, Truss Head Tek Self Drilling Screw are frequently chosen for fastening sheet metal and other material types that have large holes. The wide head of the screw works to cover holes that are larger than the body of the screw for an attractive finish. The dome shape of the heads of truss Screws is low enough to use for most projects, but an advantage is that the screws are difficult to remove or tamper with. Another advantage of a truss screw is that the wide head prevents it from sinking too deeply into the material and causing tearing.



Diameter Size:	#6(M3.5)	#8(M4.2)	#10(M4.8)
Head Dia	7.4mm	7.9mm	9.5mm
Head Height	1.8mm	2.2mm	2.5mm
			1/2"
			5/8"
Length	3/8"		3/4"
	1/2"	1/2"	7/8"
		5/8"	1"
		3/4"	1-1/4"
			1-1/2"
			1-3/4"
			2"

### Surface Treatment

- 1.White zinc plated
- 2.Blue-white zinc plated
- 3.Yellow zinc plated

Material: steel c1022





# HeBei DeLong Fastener Manufacturing Co.,Ltd

## Pan Head Self Drilling Screw

All Points Fasteners' pan head self-drilling Screws feature a lower profile than oval or round screws, a flat or slightly rounded top and sharp vertical edges. Their unique design is suitable for high-torque installations into wood or metal. Use them for all general purpose applications including construction, other installations, roofing and more.

Finish: Zinc , Plain

Material:C1022  
Measurement system: Metric  
Head Style:Pan  
Place of Origin: HanDan, China



Brand Name: DL  
Standard:ISO/JIS/ANSI/GB/ISO  
Product name:Self drilling Screw  
Color:Black/white/blue/yellow/grey  
Port:Tianjin / QingDao,China

Packing:Bulk Packed,box ctn, pallet, customized

Size would follow the standard, for large quantity we also can accept the customization

Applications :skin sheet to steel residential steel frame construction for light duty purpose suitable for stitching 1thick&1thin steel features pan head design on using non walk point provides fast material engagement

Dia Size	#6(M3.5)	#8(M4.2)	#10(M4.5)
Head Dia	6.9mm	8.2mm	9.5mm
Head Height	2.6mm	3.1mm	3.6mm
	3/8"	3/8"	
	1/2"	1/2"	1/2"
Length	5/8"	5/8"	5/8"
	3/4"	3/4"	3/4"
	1"	1"	1"
	1-1/4"	1-1/4"	1-1/4"
	1-1/2"	1-1/2"	1-1/2"
	2"	1-3/4"	1-3/4"
		2"	2"





# HeBei DeLong Fastener Manufacturing Co.,Ltd

## Countersunk Head Self Drilling Screw

Csk Phillips head self-drilling Screws Countersunk head Self Drilling Screw are high strength and durable fasteners used for sheet metal applications. To provide a perfect assembly, the countersunk variation of the philip screw has to be used in conjunction with a countersunk hole. The usage of these screws requires a pre-drilled hole. The screws themselves are threaded with twisted gradation which makes it easy to install on the pilot hole. This allows the screws to be used in high-precision applications like machine and electrical component assembly



Dia Size	#6(M3.5)	#8(M4.2)	#10(M4.5)	#12(M5.5)	#14(M6.3)
Head Dia	6.8mm	8.1mm	9.5mm	10.8mm	12.4mm
Head Height	2.1mm	2.5mm	3.0mm	3.4mm	3.8mm
	3/8"			3/4"	
	1/2"	1/2"		1"	
Length	5/8"	5/8"	5/8"	1-1/4"	7/8"
	3/4"	3/4"	3/4"	1-1/2"	1-1/2"
	1"	1"	1"	1-3/4"	2"
		1-1/4"		2"	2-1/2"
		1-1/2"	1-1/2"	2-1/2"	
		1-3/4"	1-3/4"		
		2"	2"		
		2-1/2"	2-1/2"		

### Surface Treatment

- 1.White zinc plated
- 2.Blue-white zinc plated
- 3.Yellow zinc plated

Countersund Head Self Drilling Screw packing : Bulk, Woven Bag , Box+Carton,Pallet .





## HeBei Delong Fastener Manufacturing Co.,Ltd

---

Contact Person : Mrs Cally

Add:Dong Ming Yang Village ,YongNian District, HanDan City,HeBei Province, China.

Website : [www.delongfastener.com](http://www.delongfastener.com)

Whats App/Wechat: +8615932307696

Mobile : +8615031095552

Email: [cally@delongfastener.com](mailto:cally@delongfastener.com)



[www.delongfastener.com](http://www.delongfastener.com)